

## **LISTING OF THE CLAIMS**

There are no amendments to the claims, but this listing of claims as they currently stand is provided for the convenience of the Examiner:

### **Listing of Claims:**

1. (Previously Presented) A lock mechanism for use with a component to be locked by the mechanism and which is securable to the lock mechanism or is releasable therefrom, which lock mechanism comprises:

- a housing having a bore;
- a retaining member slidably received in said bore for movement between a first position where the retaining member is engageable with said component and a second position where the retaining member is disposed deeper in the bore and cannot be disengaged from said engaged component;
- a catch member movable between active and inactive positions, said catch member being in its inactive position when the retaining member is in its first position but on moving the retaining member to its second position the catch member moves to its active position engaged with the retaining member to hold the retaining member in its second position, and on moving said catch member back to its inactive position again the retaining member is freed for movement to its first position;
- an auxiliary lock for the retaining member, said auxiliary lock being operable to hold the retaining member in its second position irrespective of operation of the catch member to its inactive position;
- an indicator for indicating the locking condition of the mechanism and having at least two indicating states; and
- an electronic control unit driving said indicator and having an input derived from said catch member to indicate when the catch member is in its active position, said control unit further being responsive to an external signal to effect sealing of the lock mechanism and to operate the auxiliary lock, whereby a first indicating state of the indicator shows whether sealing of the lock

mechanism is intact and a second indicating state shows whether an attempt has been made to release the lock mechanism since the lock mechanism was last sealed.

2. (Previously Presented) A lock mechanism as claimed in claim 1, wherein the auxiliary lock includes a bolt having locked and free positions, said bolt in its locked position engaging the retaining member to prevent movement thereof from its second position, and the bolt when in its free position permitting the retaining member to move to or from its first position.

3. (Previously Presented) A lock mechanism as claimed in claim 2, wherein said bolt comprises a plate slidably mounted in the housing and having an aperture, said retaining member passing through said aperture and having a recess engaged by said plate when in its locked position.

4. (Previously Presented) A lock mechanism as claimed in claim 2, wherein said bolt comprises a plunger mounted within the housing, said plunger when in its locked position engaging a circumferential groove formed in the retaining member.

5. (Previously Presented) A lock mechanism as claimed in claim 2, wherein a power-driven actuator is provided to cause movement of the bolt between its said locked and free positions, the operation of the actuator being controlled by the control unit.

6. (Original) A lock mechanism as claimed in claim 5, wherein sealing of the lock mechanism causes the bolt to be moved to its locked position to prevent subsequent movement of the retaining member to its first position until the lock mechanism has been unsealed.

7. (Previously Presented) A lock mechanism as claimed in claim 1, wherein the indicator has a third indicating state corresponding to the retaining member being in its second position and the catch member in its active position, but the auxiliary lock has not been operated to hold the retaining member in its second position.

8. (Original) A lock mechanism as claimed in claim 7, wherein the indicator has a fourth indicating state corresponding to movement of the catch member to its inactive position following sealing of the lock mechanism by the auxiliary lock, whereby the retaining member is not freed to move to its first position.

9. (Previously Presented) A lock mechanism as claimed in claim 1, wherein the indicator has at least two indicator lights the illumination whereof is controlled by the control unit.

10. (Previously Presented) A lock mechanism as claimed in claim 1, wherein the control unit includes a card reader for reading information carried on a card, whereby sealing of the lock mechanism may be performed by a person in possession of a suitable card.
11. (Original) A lock mechanism as claimed in claim 10, wherein the control unit is arranged to permit initial sealing of the mechanism by a first card carrying appropriate information, and resealing by a second card carrying appropriate but different information.
12. (Previously Presented) A lock mechanism as claimed in claim 1, wherein the control unit includes a receiver for electromagnetic waves of a defined frequency whereby sealing of the lock mechanism may be performed remotely by a suitably tuned transmitter transmitting waves appropriately encoded to perform sealing of the lock mechanism.
13. (Previously Presented) A lock mechanism as claimed in claim 1, wherein said component is in the form of a flexible cable having at one end an enlarged head engageable with the retaining member.
14. (Previously Presented) A lock mechanism as claimed in claim 1, wherein the retaining member is in the form of a U-shaped shackle one end of which is free of the housing when the retaining member is in its first position, said one end being received in a further bore in the housing when the retaining member is in its second position.
15. (Previously Presented) A lock mechanism as claimed in claim 1, wherein the retaining member has an intermediate portion of reduced cross section and which remains in the bore in the housing when the retaining member is in its first position, the catch member being slidably mounted in a bore extending transversely to and partially intersecting the bore in which the retaining member is received, the catch member having large and small diameter parts which when aligned with the retaining member bore correspond respectively to the active and inactive positions of the catch member.
16. (Previously Presented) A lock member as claimed in claim 15, wherein the catch member is spring-urged to its active position.
17. (Previously Presented) A lock mechanism as claimed in claim 1 and including an electrical switch operable on movement of the catch member between its two positions and connected to the control unit to furnish said input thereto.

Serial No. 10/599,198  
Filed: September 22, 2006  
Page 5 of 9

Examiner: Christopher J. Boswell  
Group Art Unit: 3673

18. (Previously Presented) The combination of a lock mechanism as claimed in claim 1 and a goods compartment having an access opening provided with a door to close that opening, wherein the retaining member is engageable with a component associated with the compartment door, thereafter to prevent opening of the door.